

BioSentry Visimaster - Visitor Kiosk (10.1 inch)



* The stand shown in the picture is an additional accessory and not part of standard supply.

Base Station

Operating System : **Android 11, Red Velvet Cake**
Processor : **Quad Core A55 1.8Ghz 64bit Processor**
Memory : **2 GB DDR4 RAM, 8GB built-in-storage**

Access Control

Potential Free Contacts : **NO-COM-NC Relay 7 Amp Contact capacity**
Door Open Sensor : **Optional**

Display & Touch

- **10.1 inch, 1280*800, 10 Point Capacitive** • **Touch LCD Display**
- **16:10 Screen Ratio**

HMI

Audio, Touch & Display : **Built in USB Host and OTG**
Camera : **5MP Auto Focus MiPi**

Power

Input (Power Adaptor) : **230 V AC 50 HZ for Power Adaptor**
Power Adaptor Output : **12V DC / 3 Amp**

Device Management

Firmware Update : **OTA**
Access Control Open/Close time : **Software Configurable**
Audio instruction Language : **Selectable (English Default)**

Connectivity

Ethernet (POE), Wi-Fi 802.11 b/g/n
GSM/SIM card : **Not provisioned**

Cloud Connect

*.visiapp.in
OEM Option to choose customised portal

Enclosure

Vandal Proof, Industrial, Rugged, IP40, ABS Body,
Mounting Bracket for Vertical Wall provided

Environmental

Operating Temperature & RH
5 to 47 Degrees Celsius, RH 95%

Weight and Dimensions

660 grams, 258 mm X 176 mm X 27 mm