

SmartSentry ETH- Smart Card Biometric Attendance Device



Base Station

Operating System : **Android 11, Red Velvet Cake**
Processor : **Quad Core ARM Cortex-A55 64bit processor**
Memory : **2 GB RAM, 8GB built-in-storage**

Access Control (Optional)

Potential Free Contacts : **NO-COM-NC Relay 7 Amp Contact capacity**
Door Open Sensor : **Optional**

Display & Touch

Full Capacitive Multi-Touch 5 Inch IPS (800*480)

HMI

Audio, Touch & Display : **Built in**

Device Management

Firmware Update : **OTA**
Access Control Open/Close time : **Software Configurable**
Audio instruction Language : **Selectable (English Default)**
Shift Detections : **Auto work Shift detection**

Smart Card Reader

Operating Frequency : **13.56 MHz**
Read Range : **Up to 50 mm**
Standard / Protocols : **ISO 14443A**

Power

Input (Power Adaptor) : **110-260V AC**
Battery Backup : **NO (External-Optional)**
Power Adaptor : **12V DC / 3 Amp**

Connectivity

Ethernet, Wi-Fi 802.11n

Enclosure

Vandal Proof, Industrial, Rugged, IP40, ABS Body,
Mounting Bracket for Vertical Wall provided

Cloud Connect

presence.attendanceportal.com
OEM Option to choose customised portal

Environmental

Operating Temperature & RH 5 to 47
Degrees Celsius, RH 95%

Weight and Dimensions

500 grams, 225 mm X 100 mm X 30 mm